

## SPECIFICATIONS

L.O.A\* : 9.25 m  
Length of hull : 8.00 m  
Width of hull : 3.10 m  
Weight : 3 800 kg  
Draft : 0.85 m  
Minimum air draught on sea : 2.50 m  
Fuel tank capacity : 450 l  
Water tank capacity : 135 l  
Engine : single or twin-engined diesel  
Maximum engine power single engine : 315 HP  
Maximum engine power twin-engined : 2 x 175 HP  
Transmission : propeller shaft  
EC certification : B8 / C10  
Architects : Joubert-Nivelt  
Designer : Bertrand Danglade  
\* with swimming platform and bow-fishing gangway options

## STANDARD EQUIPMENT

### Construction

Superstructure : cellular sandwich  
Hull bottom : balsa sandwich  
Deck: 12 mm marine ply sandwich  
Hull and deck reinforced polyester laminate  
Wooden bulwark rail and rubbing strakes  
Stainless steel keel strip

### Deck facilities

Walkaround deck layout  
Self-draining chain locker  
Stem-head anchor roller  
2 fairleads forward and aft  
2 mooring cleats fore and aft  
6 handrails on coachroof and wheelhouse  
Stainless bow pulpit  
2 dorade cabin ventilators  
Recessed fuel filler  
Eyelets for fenders

### Engine facilities

Diesel engine, prop shaft drive with protected propeller  
Soundproofed engine compartment  
450-litre fuel tank

### Cockpit & deck

Self-draining cockpit  
Transom door  
1 stern locker (access to hydraulic steering ram)

1 hatch above saloon  
1 sliding side door  
1 sliding aft door  
3 folding slatted benches  
1 engine casing  
1 emergency tiller  
2 rod-holders  
1 aft cockpit locker converts to live fi sh well (option)  
Manual bilge pump  
Bathing ladder

### Wheelhouse

14 safety-glass windows, one opening  
Instrument console  
Steering compass  
1 electric windscreen wiper  
1 hydraulic steering wheel  
Engine controls  
Helmsman's seat adjustable fore-and-aft  
Chart table with stowage  
Bi-fold doors for forward cabin  
Floor hatch to bilge locker  
U-shaped dinette converting into double berth  
Adjustable (height) dinette table  
Opening port in head

### Galley

Sink with pressurised water  
2-burner cooker  
135-litre fresh-water tank  
65-litre refrigerator  
Cupboards

### Forward cabin

V-shaped double berth  
Lockers below berth  
Opening hatch & two portholes  
Hanging space – Cubby-holes for stowage  
Head : shower/wash-basin/toilet/Holding tank  
Opening port in head

### Electrical facilities

1 x 12 volt, 105 amp battery per engine  
2 x 12 volt, 105 amp battery for services  
Electrical distribution panel  
Cabin, head and wheelhouse lighting  
Navigation lights  
Bilge pump